

HiBoard-ISME

Wireless Projector for Dahua Vision's Intelligent Conference Tablet

· One-click projection.



Environment Requirements

Operating temperature	0°C–40°C
Operating humidity	10%–90%, without condensation
Transmission distance	The distance between wireless projectors and the host is up to 12 m
Frequency band	2.4 GHz and 5 GHz (recommended)

Product Overview

HiBoard-ISME is used with Dahua Vision' Intelligent Conference Tablet HiBoard-IE Series.

Technical Specification

System config

Number of input sources connected at the same time	8
Interface	USB2.0*1
Input voltage	5V DC
Power consumption	0.85 W
Transmission delay	> 65 ms
Operating system	Windows 7, Windows 8, Windows 8.1, and Windows 10; Mac OS 10.10 to 10.13
Frame Rate	Windows 7: 1920 × 1080 @ 20 fps/1366 × 768 @ 20 fps Windows 8 (8.1)/OSX: 1920 × 1080 @ 30 fps/1366 × 768 @ 30 fps Windows 10: 1920 × 1080 @ 30 fps/1366 × 768 @ 30 fps

Structure

Net weight	0.1 kg
Dimensions (L × W × T)	178.7 mm × 77 mm × 21.3 mm
Packing dimensions (L × T × H)	210 mm × 111 mm × 44 mm